

SPECIFICATION NOTES

SYSTEM
METAL TECHNOLOGY 5-20 HI THERMALLY BROKEN ALUMINIUM WINDOWS.
REYNOBOND COMPOSITE RAINSCREEN CASSETTES.

FINISH - WINDOW OUTER & CILL FLASHING
ALL VISIBLE ALUMINIUM FACES POLYESTER POWDER COATED RAL 7012 MATT (30% GLOSS) 40 MICRON.

FINISH - WINDOW INNER
ALL VISIBLE ALUMINIUM FACES POLYESTER POWDER COATED RAL 9010 MATT (30% GLOSS) 40 MICRON.

GLAZING - G1 - VISION
OUTER - 6MM CLEAR TOUGHENED SOFT COAT LOW E.
CAVITY - 16MM ARGON FILLED WITH SILVER SPACER BARS.
INNER - 6MM CLEAR TOUGHENED.
U VALUE = 1.1 W/m2K (CENTRE PANE).
TOUGHENED GLASS NOT HEAT SOAK TESTED.

GLAZING - P1 - PANELS
OUTER - 1.5MM ALUMINIUM SKIN RAL 9010 MATT (30% GLOSS).
CORE - 25MM STYROFOAM.
INNER - 1.5MM ALUMINIUM SKIN RAL 9010 MATT (30% GLOSS).
U VALUE = 0.77 W/m2K (CENTRE PANE)

GLAZING - P2 - PANELS
OUTER - 1.5MM ALUMINIUM SKIN RAL 7012 MATT (30% GLOSS).
CORE - 25MM KINGSPAN TP10 RIGID INSULATION.
INNER - 1.5MM ALUMINIUM SKIN RAL 9010 MATT (30% GLOSS).
U VALUE = 0.77 W/m2K (CENTRE PANE)


CLADDING - R1
ALUMINIUM COMPOSITE PANEL, SMOKE SILVER METALLIC DURAGLOSS 5000 SATIN.

POINTING
ALL PERIMETER POINTING IN LOW MODULUS SILICON, BLACK.

HARDWARE - SIDE HUNG WINDOWS
GENERAL SYSTEM FITTINGS ALL IN SILVER FINISH.
CONCEALED HINGES.
LOCKING HANDLES IN SAA, FITTED MID VENT HEIGHT.
NO RESTRICTORS.

HARDWARE - TILT TURN WINDOWS
GENERAL SYSTEM FITTINGS ALL IN SILVER FINISH.
CONCEALED HINGES.
LOCKING HANDLES IN SAA, ALLOWING TILT BUT NOT TURN UNLESS UNLOCKED, FITTED MID VENT HEIGHT.
NO RESTRICTORS.

GENERAL
ALL DRAIN CAPS IN BLACK PLASTIC.
TRICKLE VENTS, SIMON AIRSTRIP 19000 WITH KNOB CONTROL.



ISSUED FOR
APPROVAL

FILE 855...

-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
Rev	Date	Notes

Description:

SPECIFICATION

Project:

GRENFELL TOWER
GRENFELL RD, LONDON. W11 1TQ

Drawn By:
bd KVL

Date:
15.01.15

Scale:
1:2@A3

harley
HARLEY HOUSE
BROOKLANDS PARK
FARNINGHAM ROAD
CROWBOROUGH
EAST SUSSEX
TN6 2JD
Tel: [REDACTED]

Drawing No:
C1059-100

Rev:
-